

## This course covers Cortex-A7 ARM CPU

### OBJECTIVES

- This course is split into 3 important parts:
  - Cortex-A7(MP) architecture
  - Cortex-A7(MP) software implementation and debug
  - Cortex-A7(MP) hardware implementation.
- Introduction to Hypervisor new privilege mode is done at the beginning of this course.
- The consequences on address translation is then explained, introducing the 2-stage translation.
- Decoupling guest OS from hardware using traps to Hypervisor is studied.
- The course also details the new features of the Generic Interrupt Controller v2, explaining how physical interrupt requests can be virtualized.
- The course details the new approach regarding integrated timers / counters.
- AXI v4 new capabilities are highlighted with regard to AXI v3.
- Through sequences involving a Cortex-A15MP and a Cortex-A7MP, the hardware coherency is studied, explaining how snoop requests can be forwarded by CCI-400 interconnect.
- Implementation of I/O MMU-400 is also covered.

*A more detailed course description is available on request at [training@ac6-training.com](mailto:training@ac6-training.com)*

### PREREQUISITES AND RELATED COURSES

- More than 12 correct answers to Cortex-A prerequisites questionnaire.
- Related courses:
  - Programming with RVDS IDE, reference [RV0 - Programming with RVDS IDE](#) course
  - VFP programming, reference [RC0 - VFP programming](#) course
  - NEON programming, reference [RC1 - NEON-v7 programming](#) course

### Course Environment

- Theoretical course
  - PDF course material (in English) supplemented by a printed version for face-to-face courses.
  - Online courses are dispensed using the Teams video-conferencing system.
  - The trainer answers trainees' questions during the training and provide technical and pedagogical assistance.
- At the start of each session the trainer will interact with the trainees to ensure the course fits their expectations and correct if needed

### Target Audience

- Any embedded systems engineer or technician with the above prerequisites.

### Evaluation modalities

- The prerequisites indicated above are assessed before the training by the technical supervision of the trainee in his company, or by the trainee himself in the exceptional case of an individual trainee.
- Trainee progress is assessed by quizzes offered at the end of various sections to verify that the trainees have assimilated the points presented

- At the end of the training, each trainee receives a certificate attesting that they have successfully completed the course.
  - In the event of a problem, discovered during the course, due to a lack of prerequisites by the trainee a different or additional training is offered to them, generally to reinforce their prerequisites, in agreement with their company manager if applicable.

## Plan

### First day

#### **OVERVIEW OF CORTEX-A7MP**

- Cortex-A7 architecture
- Organization of a SoC based on Cortex-A7MP
- AMBA4 coherent interconnect capabilities
- I/O MMU
- 64-Byte cacheline size, integrated L2 cache
- VFPv4 and SIMDv2
- Supported instruction sets
- Highlighting differences between Cortex-A9 and Cortex-A7

#### **INSTRUCTION PIPELINE**

- Global organization, dual issue capability
- Fetch / decode / issue / writeback stages
- Data processing unit
- Branch accelerators

#### **INTRODUCTION TO HYPERVISOR STATE**

- Processor privilege levels state machine, user, guest OS, hypervisor
- Detailing the various operation modes (Bare-Metal, Hypervisor kernel and user task, Hypervisor with Guest partition)
- Objective of the Hypervisor
- Support for interrupt nesting in Hypervisor mode
- Detecting VFP/Neon utilization by a Guest partition

#### **EXCEPTION MECHANISM**

- Hypervisor vector table
- Utilization of Vector #5 to trap Guest partition events
- Virtual Interrupt and Abort bits control, IRQ, FIQ, external abort routing control
- Taking exceptions into Hypervisor mode

#### **GENERIC INTERRUPT CONTROLLER (GICv2)**

- Integration in a SoC based on Cortex-A15MP and Cortex-A7MP
- Highlighting the new features with regard to Cortex-A9MP
- Steering interrupts to guest OS or Hypervisor
- Virtual CPU interface
- Split EOI functionality
- Deactivating an interrupt source from the Virtual CPU interface

### Second day

#### **VIRTUALIZATION EXTENSIONS**

- New Intermediate Physical Address, 2-stage address translation
- Memory translation system

- Memory management when running in hypervisor mode
- Exposing the MMU to Other Masters, IO MMU
- Emulation support, trapping load and store and executing them in Hypervisor state
- Additional security facilities

## **LARGE PHYSICAL ADDRESS EXTENSIONS SPECIFICATION (LPAE)**

- New 3-level system
- Hypervisor-level address translation
- Level-1 table descriptor format
- Level-2 table descriptor format
- Attribute and Permission fields in the translation tables
- Handling of the ASID in the LPAE
- New cache and TLB maintenance operations

## **MMU IMPLEMENTATION**

- TLB organization, L1-TLB, L2-TLB
- Coherent table walk
- Tablewalk cache and IPA cache operation
- Determining the exact cause of aborts through status registers
- Behavior when MMU is disabled
- TLB maintenance operations

## **OS SUPPORT SYNCHRONIZATION OVERVIEW**

- Inter-Processor Interrupts
- Barriers
- Cluster ID
- Exclusive access monitor, implementing Boolean semaphores
- Global monitor
- Spin-lock implementation
- Using events

## **Third day**

## **LEVEL ONE SUBSYSTEM**

- Cache organization, 2-way instruction cache, 4-way data cache
- Speculative accesses
- Hit Under Miss, Miss under Miss
- Read allocate mode
- Uploading the contents of L1 caches through dedicated CP15 registers
- MOESI data cacheline states
- Detailing cache maintenance operations

## **LEVEL TWO SUBSYSTEM**

- Optional L2 Cache
- Read allocate mode
- ACE master interface
- By means of sequences involving a multi-core Cortex-A7 and external masters, understanding how snoop requests can be used to maintain coherency of data between caches and memory
- Synchronization primitives, the 3 levels of monitors

## **GENERIC TIMER**

- ARM generic 64-bit timers for each processor
- Virtual time vs Physical time

- Event stream purpose
- Kernel event stream generation
- Hypervisor event stream generation

## PERFORMANCE MONITORING VIRTUALIZATION EXTENSIONS

- Hypervisor performance monitoring
- Guest OS performance monitoring
- Reducing the number of counters available to a Guest OS
- Fully virtualizing the PMU identity registers

## Fourth day

## AMBA4

- AXI-4
- AXI-4 stream protocol
- AXI-4 lite
- AXI Coherency Extension (ACE)
- Exported barriers

## HARDWARE IMPLEMENTATION

- Clock domains
- Resets, power-on reset timing diagram
- Power domains
- Power-on reset sequence, soft reset sequence
- Power management, WFI / WFE, dormant mode based on L2 memory
- Interface to the Power Management Unit
- Powering down a CPU
- External debug over power down

## CCI-400 CACHE COHERENT INTERCONNECT

- AMBA 4 snoop request transport
- Snoop connectivity and control
- ACE master interface
- Connecting 2 CPUs through CCI, managing coherency domains
- Example of Cortex-A7 dual core and Cortex-A15 dual core

## CORESIGHT DEBUG

- Program Trace Macrocell
- Cross Trigger Interface and Cross Trigger Matrix for multi-processor debugging
- Adding Virtual Machine ID in the criterion used to set a breakpoint / watchpoint

## Renseignements pratiques

**Inquiry : 4 days**