

This course covers the Cortex-A17 cluster

OBJECTIVES

- This course is split into 3 important parts:
 - Cortex-A17 architecture
 - Cortex-A17 software implementation and debug
 - Cortex-A17 hardware implementation.
- Introduction to Hypervisor new privilege mode is done at the beginning of this course.
- The consequences on address translation is then explained, introducing the 2-stage translation.
- Decoupling guest OS from hardware using traps to Hypervisor is studied.
- The course also details the new features of the Generic Interrupt Controller v2, explaining how physical interrupt requests can be virtualized.
- The course details the new approach regarding integrated timers / counters.
- AXI v4 new capabilities are highlighted with regard to AXI v3.
- Through sequences involving a Cortex-A17 and a Cortex-A7MP, the hardware coherency is studied, explaining how snoop requests can be forwarded by CCI-400 interconnect.
- Implementation of I/O MMU-400 is also covered.

A more detailed course description is available on request at training@ac6-training.com

PREREQUISITES AND RELATED COURSES

- Knowledge of Cortex-A9.
- More than 12 correct answers to Cortex-A prerequisites questionnaire.
- Related courses:
 - VFP programming, reference cours [RC0 - VFP programming](#)
 - NEON programming, reference cours [RC1 - NEON-v7 programming](#)

Environnement du cours

- Cours théorique
 - Support de cours au format PDF (en anglais) et une version imprimée lors des sessions en présentiel
 - Cours dispensé via le système de visioconférence Teams (si à distance)
 - Le formateur répond aux questions des stagiaires en direct pendant la formation et fournit une assistance technique et pédagogique
- Au début de chaque demi-journée une période est réservée à une interaction avec les stagiaires pour s'assurer que le cours répond à leurs attentes et l'adapter si nécessaire

Audience visée

- Tout ingénieur ou technicien en systèmes embarqués possédant les prérequis ci-dessus.

Modalités d'évaluation

- Les prérequis indiqués ci-dessus sont évalués avant la formation par l'encadrement technique du stagiaire dans son entreprise, ou par le stagiaire lui-même dans le cas exceptionnel d'un stagiaire individuel.

- Les progrès des stagiaires sont évalués par des quizz proposés en fin des sections pour vérifier que les stagiaires ont assimilé les points présentés
- En fin de formation, une attestation et un certificat attestant que le stagiaire a suivi le cours avec succès.
 - En cas de problème dû à un manque de prérequis de la part du stagiaire, constaté lors de la formation, une formation différente ou complémentaire lui est proposée, en général pour conforter ses prérequis, en accord avec son responsable en entreprise le cas échéant.

Plan

OVERVIEW OF CORTEX-A17

- Cortex-A17 architecture
- Organization of a SoC based on Cortex-A17
- AMBA4 coherent interconnect capabilities
- Inner Shareable vs Outer Shareable attribute
- I/O MMU
- 64-Byte cacheline size, integrated L2 cache
- VFPv4 and SIMDv2
- Highlighting differences between Cortex-A9 and Cortex-A17

INSTRUCTION PIPELINE

- Global organization, dual issue capability
- Fetch / decode / rename / dispatch stages
- Loop mode
- Execution clusters
- Out-of-order execution
- Branch accelerators

INTRODUCTION TO HYPERVISOR STATE

- Processor privilege levels state machine, user, guest OS, hypervisor
- Detailing the various operation modes (Bare-Metal, Hypervisor kernel and user task, Hypervisor with Guest partition)
- Asymmetric approach, no support for Virtualization of Secure state functionality
- SVC, HVC and SMC instructions
- Objective of the Hypervisor
- Hypervisor related instructions and registers
- List of registers that have to be saved / restored to be able to suspend / resume a guest partition
- Accessing banked registers or any Non-Secure mode while running in Hypervisor mode

EXCEPTION MECHANISM

- Hypervisor vector table
- Utilization of Vector #5 to trap Guest partition events
- System Call into Hypervisor mode
- Asynchronous exceptions
- Virtual Interrupt and Abort bits control, IRQ, FIQ, external abort routing control
- Hypervisor exception return
- Taking exceptions into Hypervisor mode

GENERIC INTERRUPT CONTROLLER (GICv2)

- Integration in a SoC based on Cortex-A17 and Cortex-A7
- Highlighting the new features with regard to Cortex-A9
- Steering interrupts to guest OS or Hypervisor
- Virtual CPU interface
- Split EOI functionality
- Deactivating an interrupt source from the Virtual CPU interface
- Front-end interface accessed by the Guest Kernel

- Back-end interface accessed by the Hypervisor

VIRTUALIZATION EXTENSIONS

- New Intermediate Physical Address, 2-stage address translation
- Memory translation system
- Memory management when running in hypervisor mode
- Virtual Machine Identification
- Exposing the MMU to Other Masters, IO MMU
- Emulation support, trapping load and store and executing them in Hypervisor state
- Second-stage access permissions and attributes

LARGE PHYSICAL ADDRESS EXTENSIONS SPECIFICATION (LPAE)

- Need to introduce support for a second stage of translation as part of the Virtualization Extensions
- New 3-level translation
- Level-1 table descriptor format
- Level-2 table descriptor format
- Attribute and Permission fields in the translation tables
- Improving the caching of translation entries by providing contiguous hints
- complete set of cache allocation hints
- Handling of the ASID in the LPAE
- New cache and TLB maintenance operations

MMU IMPLEMENTATION

- TLB organization, L1-TLB, L2-TLB
- TLB match process
- Coherent table walk
- Determining the exact cause of aborts through status registers
- Behavior when MMU is disabled

OS SUPPORT – SYNCHRONIZATION OVERVIEW

- Inter-Processor Interrupts
- Barriers
- Cluster ID
- Exclusive access monitor, implementing Boolean semaphores
- Global Monitor
- Spin-lock implementation
- Using events
- Indicating the effect of Multi Core on debug interfaces

LEVEL ONE SUBSYSTEM

- Physically Indexed Physically Tagged caches
- Pseudo LRU replacement algorithm
- Speculative accesses
- Hit Under Miss, Miss under Miss
- Write streaming threshold definition
- L1 cache hardware prefetch
- MOESI data cacheline states

LEVEL TWO SUBSYSTEM

- Cache organization
- Optional ECC protection
- L2 cache hardware flush
- ACE master interface
- ACMP master interface
- ACP slave interface

- By means of sequences involving a multi-core Cortex-A17 and external masters, understanding how snoop requests can be used to maintain coherency of data between caches and memory

GENERIC TIMER

- ARM generic 64-bit timers for each processor
- Virtual time vs Physical time
- Effect of virtualization on these timers
- Event stream purpose
- Kernel event stream generation
- Hypervisor event stream generation
- Gray count timer distribution scheme

PERFORMANCE MONITORING VIRTUALIZATION EXTENSIONS

- Hypervisor performance monitoring
- Guest OS performance monitoring
- Lazy switching of PMU state by a hypervisor
- Reducing the number of counters available to a Guest OS
- Fully virtualizing the PMU identity registers

AMBA4

- AXI-4
 - Quality of Service signaling
 - Updated meaning of Read Allocate and Write Allocate
 - Transaction buffering
- AXI-4 stream protocol
 - Byte types, data, position, null
 - Byte stream
 - Sparse stream
 - Data merging, packing, and width conversion
- AXI-4 lite
 - Burst length of 1
 - No exclusive access support
- AXI Coherency Extension (ACE)
 - Shareability domains
 - Coherency model, cache states
 - Additional channel signals
 - New channels, snoop address, snoop response, snoop data
 - Studying through sequences how a load request and a store request will be handled whenever they are marked as outer shareable requests
 - Using ReadUnique, CleanUnique and MakeUnique requests
 - Distributed Virtual Memory (DVM)
 - DVM synchronization message
 - Selecting the coherency state machine: MESI or MOESI according to the capabilities of the interconnect
 - Snoop filtering
- Exported barriers
 - DMB / DSB inner shareable, outer shareable or system

HARDWARE IMPLEMENTATION

- Clock domains
- Resets, power-on reset timing diagram
- Valid reset combinations
- Power domains
- Power-on reset sequence, soft reset sequence
- Power management, processor and L2 state retention
- Maintaining coherency while CPUs are in standby state
- Interface to the Power Management Unit

- Powering down a CPU
- External debug over power down

CCI-400 CACHE COHERENT INTERCONNECT

- AMBA 4 snoop request transport
- Snoop connectivity and control
- Connecting 2 CPUs through CCI, managing coherency domains
- Example of Cortex-A7 dual core and Cortex-A17 dual core

CORESIGHT DEBUG

- Program Trace Macrocell
- Cross Trigger Interface and Cross Trigger Matrix for multi-processor debugging
- Adding Virtual Machine ID in the criterion used to set a breakpoint / watchpoint
- Tracking VMID change in trace output

Renseignements pratiques

Renseignements : 4 jours