

This course covers the Cortex-A73 and AARCH64

Objectifs

- This course aims to highlight the new features offered by the V8 architecture.
- It has been developed for engineers developing low level software and engineers in charge of IP hardening.
- First, an overview of Cortex-A73 is provided, to highlight the differences between a Cortex-A15/Cortex-A7 hardware platform based on CCI-400 and a Cortex-A73/Cortex-A53 hardware platform based on CCN-504.
- The new exception mechanism is described.
- The enhancements regarding the LPAE are detailed.
- New A64 assembler instructions are explained through practical examples.
- The AAPCS64 is also covered.
- The course also details the new debug ARM V8 features.
- Cortex-A73 hardware implementation is explained, particularly the low power states.

Prerequisites and related courses

- Knowledge of a 32-bit ARM CPU is recommended
- See also cours [RI0 - AXI3 / AXI4 INTERCONNECT](#) and cours [RC1 - NEON-v7 programming](#) that describes the advanced SIMD (NEON) architecture and instruction set

Environnement du cours

- Cours théorique
 - Support de cours au format PDF (en anglais) et une version imprimée lors des sessions en présentiel
 - Cours dispensé via le système de visioconférence Teams (si à distance)
 - Le formateur répond aux questions des stagiaires en direct pendant la formation et fournit une assistance technique et pédagogique
- Au début de chaque demi-journée une période est réservée à une interaction avec les stagiaires pour s'assurer que le cours répond à leurs attentes et l'adapter si nécessaire

Audience visée

- Tout ingénieur ou technicien en systèmes embarqués possédant les prérequis ci-dessus.

Modalités d'évaluation

- Les prérequis indiqués ci-dessus sont évalués avant la formation par l'encadrement technique du stagiaire dans son entreprise, ou par le stagiaire lui-même dans le cas exceptionnel d'un stagiaire individuel.
- Les progrès des stagiaires sont évalués par des quizz proposés en fin des sections pour vérifier que les stagiaires ont assimilé les points présentés
- En fin de formation, une attestation et un certificat attestant que le stagiaire a suivi le cours avec succès.
 - En cas de problème dû à un manque de prérequis de la part du stagiaire, constaté lors de la formation, une formation différente ou complémentaire lui est proposée, en général pour conforter ses prérequis, en accord avec son responsable en entreprise le cas échéant.

Plan

First Day

Overview of Cortex-A73

- Cortex-A73 architecture
- Intra-cluster cache coherency
- Inter-cluster cache coherency through AXI4 ACE
- ACP port
- Programmer's model

Introduction to ARM Architecture V8

- Enhancement with regard to AArchv7
- Register mapping between A32/T32 and A64
- Mapping of AArch64 System registers to the AArch32 System registers

ARMv8 Exceptions

- Four exception levels
- Exception Link Registers
- Register banking by exception level based on a new exception model
- Nesting on the same exception level
- Exception type and exception origin
- Syndrome registers used to provide a status information to the exception handler
- Exception return instruction

The ARMV8-A Security Model

- Security model when EL3 is using AArch64
- Trapping to EL3 using AArch64

Interprocessing

- Managing two types of processes: 64-bit and 32-bit, switching on an exception
- Non secure space organization

Second Day

Virtualization

- New hypervisor privilege level on non-secure side
- Re-entrant mode
- Hypervisor exception management, trapping
- Asynchronous exception routing and control

Instruction Pipeline

- Superscalar operation
- Predicted and non-predicted instructions
- Branch accelerators
- Invalidation and context switches
- Highlighting differences with Cortex-A57

Multicore

- Synchronization and semaphores
- Shareability memory attributes
- Operation of the global monitor
- Load acquire / Store release instruction pair
- Use of WFE and SEV instructions by spin-locks
- CLREXMON request and acknowledge signaling

Memory Accesses

- Mixed-endian support
- Program counter and stack pointer alignment
- Ordering requirements
- Page attributes : Normal or Device
- Shareability and access limitations on the data barrier operations
- Memory barriers

ARMv8 MMU Support

- LPAE enhancements to adapt to AArch64
- Supporting up to 48 bits of VA per TTBR
- Access permission checking
- Supporting up to 48 bits of IPA and PA spaces
- VMSAv8-64 address translation system
- Memory translation granule size
- Descriptor page table organization, descriptor format
- Hierarchical control of Secure or Non-secure memory accesses
- TLB preload instructions
- TLB maintenance instructions in A64
- Cortex-A73 TLB implementation

Third Day**Caches**

- Cache hierarchy, Point of Unification, Point of Coherency
- Load non temporal instruction
- Instruction and Data cache maintenance instructions in A64
- Cortex-A73 L1 and L2 memory system
- L2 hardware cache flush
- L2 replacement algorithm selection

A64 New Instruction Set

- A64 assembly language, regular bit encoding structure
- Instruction aliases
- Branches, function call and return
- Conditional select instructions, avoiding branches
- Load Store instructions, addressing modes
- Arithmetic and logical instructions, CRC calculation instructions
- Instructions for accessing AArch32 Execution environment registers

ARM Architecture Procedure Call Standard 64-bit

- General register usage convention
- Stack pointer and frame pointer
- NEON / VFP register usage convention

NEON, VFP and Cryptographic Units

- New register banking for NEON and VFP
- Mapping of the SIMD and floating-point registers between the Execution states
- Vector formats in AArch64 state
- New SIMD instructions
- Cryptography software support through a new family of instructions

GICv4

- Generic Interrupt Controller CPU interface registers
- Interrupt virtualization
- Interrupt handling to support nesting

Fourth Day

Generic Timer

- System counter clock frequency
- Physical and virtual timer count registers
- Physical up-count comparison, down-count value and timer control registers
- Virtual up-count comparison, down-count value and timer control registers

Low Power States

- Wait for Interrupt and Wait for Event
- Cortex-A73 low power modes
- L2 Wait for Interrupt
- Processor dynamic retention
- Support for power management with multiple power domains
- Dormant mode
- Processor dynamic retention
- L2 RAMs dynamic retention
- Core Q-channel interface

ARMv8 Debug

- Self-hosted debug
- Debug state instructions
- Linked comparisons for Breakpoint/Watchpoint exception generation
- Software Step exceptions
- Routing debug exceptions
- External debug, cross-triggering
- Embedded Trace Macrocell architecture

Performance Monitor

- Per-function performance monitoring at EL0 level
- Effect of EL3 and EL2 on Performance Monitor
- Event filtering

Cortex-A73 Hardware Implementation

- Clocking
- Resets

Renseignements pratiques

Renseignements : 4 jours